

[Click to Print This Page](#)



E-VISION LASER 6500 DIGITAL PROJECTOR

THE VISIONARIES CHOICE



E-Vision Laser 6500 II WUXGA

6,500 Lumens | Contrast Ratio: 20,000:1 (dynamic) | Part Number: 120-061

Key Specifications:

Colour System:	Laser Phosphor / 4 Segment (RGBY) Colourwheel / 2x120Hz
Display Type:	1 x 0.67" DarkChip™ DMD™
DMD Specification:	1920 x 1200 pixels native display. Fast transit pixels for smooth greyscale and improved contrast.
Aspect Ratio:	16x10
Fill Factor	87%
Key Features:	Video & Graphics Processing • HDMI 1.4 for Side by Side, Frame Packing & Top Bottom 3D Formats. • Dual Flash Processing can be used to multiply the displayed frame rate for 3D sources (example 144Hz display). • Synchronisation of active glasses. • 24p and 1080p native display. • Sealed light engine • DICOM Simulation Mode. Geometry Correction • Cornerstone, Vertical & Horizontal Keystone. HDBaseT® Interface • Built in support for transmission of uncompressed High Definition Video over standard CAT5e/6 LAN cable.

	- Allows projector to be placed up to 100m from source with low cost cabling. - Projector Control via HDBaseT.		
Source Compatibility	HDMI including Deep Color™ processing. Graphics standards up to 1920 x 1200 resolution at 60Hz via HDMI, DVI-D, HDBaseT or VGA Component Video (SD and HD) via RGBHV.		
Inputs/Outputs	Video & Computer		
	Type	Connector	Qty
	HDMI 1.4b	HDMI	2
	DVI-D	DVI	1
	VGA / Analog RGB	15-pin D-Sub	1
	Component Video	5 x BNC	5
	HDBaseT	RJ45	1
	Video Out: VGA	15-pin D-Sub	1
	Audio In: Stereo	RCA	2
	Audio In: Stereo	3.5mm Jack	1
Audio Out: Stereo	RCA	2	
.			
Communication & Control			
Type	Connector	Qty	
3D Sync Out	Mini DIN	1	
3D Sync In	Mini DIN	1	
LAN	RJ45	1	
Serial In (RS232)	9-pin D-Sub	1	
Serial Out (RS232)	9-pin D-Sub	1	
Wired Remote In	3.5mm Stereo Jack	1	
Wired Remote Out	3.5mm Stereo Jack	1	
12V Trigger	3.5mm Stereo Jack	1	
USB (power only)	USB Type A	1	
USB (Service)	USB Type B	1	
3D Formats Supported	Frame Packing Side By Side (half) Top and Bottom		
HDTV Formats Supported	1080p (24Hz, 25Hz, 30Hz, 50Hz, 60Hz),1080i (50Hz, 60Hz), 720p (50, 60Hz)		
Computer Compatibility	Up to 1920 x 1200		
Bandwidth	165 MHz on analog RGB 165 Megapixels per second on HDMI		
Remote Control	IR remote control, wireless and wired. On-Board keypad		
Automation Control	Crestron RoomView® Connected PJLink - AMX SSDP LAN RS232 - AMX SSDP		
Colour Temperature			
Operation			
illumination Type	Laser Light Source		

Typical illumination Life	20,000 hours			
Lenses	Lens		Part No.	Optimised Focus Range*
	0.77: 1 fixed		114-785	0.4m - 3.1m
	0.77 - 1.1: 1 zoom (special order - call for info)		119-001	0.67m - 12.1m
	1.1 - 1.3: 1 zoom		116-207	1m - 9m
	1.25-1.6 zoom (special order - call for info)		119-430	1.356m - 8.078m
	1.54 - 1.93: 1 zoom		114-783	0.95m - 11.9m
	1.93 - 2.91: 1 zoom		114-784	1.2m - 29.8m
	3.0 - 5.0: 1 zoom		116-208	3m - 20m
	* Lens focal ranges above are the optimised distances but are likely to focus further, please contact your RSM for more details. Lens ratio tolerances: E-Vision Series: +/-3%. HighLite Series: +/- 5%. M-Vision Series: +/- 2%. Titan Series: +/-2%, INSIGHT Series: +/-2%,			
Lens Mount	Manual shift, zoom & focus.			
Mechanical Mounting	Front/Rear Table Front/Rear Ceiling Adjustable Front/Rear Feet			
Orientation	Table Top or Inverted: Yes Pointing Up: Yes Pointing Down: Yes Roll (Portrait): Yes			
Power Requirements	100-240VAC 50/60Hz single phase			
Power Consumption	650			
Thermal Dissipation	2218			
Fan Noise	Max 37 dBA Typical 35dBA			
Operating/Storage Temperature Operating:	Operating: 0 to 40C (32 to 104F) Storage: -20 to 60C (-4 to 140F)			
Operating Humidity	10 to 85% non-condensing			
Weight	25 kg / 55.1 lbs			
Dimensions	L: 52.5 cm W: 47 cm H: 22.05 cm L: 20.66 in W: 18.5 in H: 8.68 in			
Safety & EMC Regulations	CE, BIS, FCC Class A, UL, CCC, CB, RoHS			

Accessories	Accessory	Part No.
	Infrared Remote (replacement)	117-880
*Dimensions included for reference only and are subject to change. Please download the full set of CAD files for this display for more accurate information.		
Downloads	PDF CAD Drawings AUTOCAD Drawings STEP / IGS Drawings Lens CAD Drawings	
User Guide	User Guides Laser Risk Group Document Important Information Important Information (German) Important Information (French) Control Protocol	



DIGITAL PROJECTION, INC



55 Chastain Road, Suite 115 Kennesaw, GA.

30144



T: 770.420.1350 | F: 770.420.1360



www.digitalprojection.com



DIGITAL PROJECTION, LTD



Greenside Way, Middleton Manchester, UK

M24 1XX



T: +44.161.947.3300 | F: +44.161.684.7674



www.digitalprojection.co.uk



DIGITAL PROJECTION, INC



55 Chastain Road, Suite 115 Kennesaw, GA.

30144



Specifications subject to change without notice.
 ©2022 Digital Projection. DLP®, Digital Light Processing™ and DMD are trademarks of Texas Instruments, Inc



Certificate Number 13629
 ISO 9001



T: 770.420.1350 | F: 770.420.1360



www.digitalprojection.com



DIGITAL PROJECTION, CHINA



Rm A2301, Shaoyaoju 101 North Lane, Shi Ao

International Center, Chaoyang District, Beijing 100029,
PR China



T: +86.10.58239771 | F: +86 10 58239770