

episode®

## **EPISODE® EVOLUTION SERIES POWERED SUBWOOFER**

The Evolution Series represents our latest and greatest approach to subwoofer design. Engineering expertise meets pure power in a sealed design that produces highly accurate sound, deep bass and premium performance. Encased in a beautiful, high-gloss cabinet, these compact subwoofers can be hidden away in tight spaces, or proudly displayed.





**BUILT FOR PERFORMANCE**

Equipped with top-shelf components and Episode’s exclusive dual equalization circuitry, this subwoofer produces tight, punchy sound and deep bass – making it more musical and powerful than anything in its class!

**SEALED AND SOPHISTICATED**

A sealed design produces highly accurate sound from a form factor that’s up to 20% smaller than the competition, while a glossy cabinet and flush-mounted grille provide a premium look and feel.

**SIGNAL SENSING RESPONSIVENESS**

Either use the dedicated on/off switch or leave it in standby mode – the sub will turn off after 15 minutes of inactivity, and roar to life as soon as a signal is detected.

	ES-SUB-EVO12-BLK			ES-SUB-EVO10-BLK			ES-SUB-EVO8			ES-SUB-EVO6		
Woofer:	12" Woven Fiberglass Cone, High Temp 2" Voice Coil			10" Woven Fiberglass Cone, High Temp 1.5" Voice Coil			8" Woven Fiberglass Cone, High Temp 1.5" Voice Coil			6" Woven Fiberglass Cone, High Temp 1" Voice Coil		
Amplifier:	300 watts RMS @ 0.2% THD			200 watts RMS @ 0.2% THD			110 watts RMS @ 0.2% THD			100 watts RMS @ 0.2% THD		
Signal to Noise Ratio:	90 dB A-weighted			90 dB A-weighted			90 dB A-weighted			90 dB A-weighted		
Input Power:	100-120/220-240 VAC, ~50/60 Hz, 4A			100-120/220-240 VAC, ~50/60 Hz, 2.5A			100-120/220-240V AC, ~50/60 Hz, 1.6A			100-240V AC, ~50/60 Hz, 1.6A		
Low frequency:	-3db	-6db	-10db	-3db	-6db	-10db	-3db	-6db	-10db	-3db	-6db	-10db
	23Hz	20Hz	17Hz	28Hz	24Hz	20Hz	33Hz	28Hz	24Hz	36Hz	30Hz	25Hz
High frequency (-3db):	200Hz			200Hz			200Hz			200Hz		
Crossover Control:	50 Hz - 200 Hz			50 Hz - 200 Hz			50 Hz - 200 Hz			50 Hz - 200 Hz		
Magnet Weight:	55.0 oz			54.0 oz			27.9 oz			13.1 oz		
Dimensions:	14.8" W x 15.4" H x 16.0" D			12.5" W x 13.1" H x 13.7" D			9.8" x 10.4" x 11.1"			8.0" W x 8.1" H x 9.1" D		
Connectors:	RCA Inputs & Gold Plated 5-Way Binding Posts			RCA Inputs & Gold Plated 5-Way Binding Posts			RCA Inputs & Gold Plated 5-Way Binding Posts			RCA Inputs & Gold Plated 5-Way Binding Posts		
Adjustments:	Volume, Crossover Frequency, Phase Control, Auto/On/Off			Volume, Crossover Frequency, Phase Control, Auto/On/Off			Volume, Crossover Frequency, Phase Control, Auto/On/Off			Volume, Crossover Frequency, 0,180 Phase, Auto/On/Off		
Weight:	34.6lbs			25.4 lbs			14.6 lbs			7.5 lbs		



For warranty info please scan QR code