



Laia Cute 10x Black/White will be the perfect option to use in medium video conference rooms, regardless of the video conferencing service you use. In addition, thanks to its 10X optical zoom you can capture all the important details for your professional video calls.

Its impressive FullHD image from its HD CMOS sensor with 2.07 effective megapixels for high-quality images up to 1920x1080 resolution with its autofocus technology will allow you to enjoy professional video conferencing from the first moment.



At the same time support two streams of stream output



Full-featured **USB** interface



1080P Full HD



H.264 Slice/ H.264 SVC encoding support



be controlled using RS232











S Skype zoom pexip[GoTo Meeting















HIGH-QUALITY HD CMOS SENSOR WITH 2.07 **EFFECTIVE MEGAPIXELS FOR HIGH-QUALITY IMAGES UP TO 1920X1080**

PROFESSIONAL WARRANTY

3 year "Prime support" warranty 24 hrs advanced replacement

FEATURES	
Video System	1080P, 720P, 540P, 480P, 360P, 240P etc.
Sensor	1/2.7", CMOS, Effective Pixel: 2.07M
Scanning mode	Progressive
Lens	10x, f5.13mm ~ 46.3mm, F1.8 ~ F2.8
Digital zoom	16x
minimal illumination	0.5 Lux @ (F1.8, AGC ON)
Shutter	1/30s ~ 1/10000s
White balance	Auto, 3000K/Indoor, 4000K, 5000K/Outdoor, 6500K_1, 6500K_2, 6500K_3, One Push, Manual
Backlight compensation	Support
Digital noise reduction	2D&3D Digital Noise Reduction
Video S/N	≥55dB
Horizontal angle of view	53.6° ~ 6.41°
Vertical angle of view	31.7° ~ 3.61°
Horizontal rotation range	±170°
Pan speed range	2.7° ~ 35.7°/s
Tilt speed range	2.7° ~ 31.5°/s
H&V flip	Support
Image freeze	Support
Number of preset	255
Preset accuracy	0.1°
USB FEATURED	0.1
Operate system	Windows 7, Windows 8, Windows 10, Mac OS X, Linux, Android
Color system / compression	YUV 4:2:2 / H.264 / MJPEG
Video format	"H.264 AVC: max to 1080P@30fps
Video iorinat	H.264 SVC: max to 1080P@30fps
	MJPEG: max to 1080P@30fps"
USB video communication	UVC 1.1~ 1.5
protocol	
UVC PTZ	Support
INPUT / OUTPUT INTERFACE	Support
USB interface	1xUSB2.0: Type B female jack
Communication interface	1xRS232 In: 8pin Min DIN, Max Distance: 30m, Protocol: VISCA/Pelco-D/Pelco-P
Power supply	JEITA type (DC IN 12V) or USB - PoC*
GENERIC SPECIFICATION	25177 type (20 114 1247 01 030 - 1 00
Input voltage	DC 12V
Current consumption	1.0A (Max)
Operating temperature	-10°C ~ 40°C (14°F ~ 104°F)
Storage temperature	-10 C ~ 40 C (14 1 ~ 104 1 7) -40°C ~ 60°C (-40°F ~ 140°F)
Power consumption	12W (Max)
MTBF	>30000h
Size	141.3mm x 153mm x 163.6mm
Net Weight	1.153 KG
Net weight	T-103 L/Q

Madrid-Spain

Headquarters: After-sale service:

Po. Europa, 26 Pta. 1 Of.3 C/Brújula, 4 Pol. Ind. PISA S.S. de los Reyes 28703 41927 Mairena del Aljarafe

Sevilla - Spain



