







# REVEL® CONCERTA SUBWOOFER-SATELLITE HOME THEATER SYSTEMS

B8 WIRELESS SUBWOOFER M8 SP2 SATELLITE SPEAKER 2-PACK M8 SP5 SATELLITE SPEAKER 5-PACK

# ABOUT REVEL CONCERTA



Revel loudspeakers are renowned the world over for their award-winning sound quality, courtesy of advanced transducer designs and proprietary acoustic technology. The Concerta Subwoofer and Satellite loudspeakers bring that legendary Revel sound to your home theater in a compact surround system that fits virtually any budget.

Designed with flexibility in mind, the M8 satellite speakers are easily placed on a shelf, and come with included wall brackets for practically unlimited mounting and positioning options. The B8 wireless subwoofer provides deep and powerful bass impact in a compact, easy-to-place form factor.

As with all Revel loudspeakers, the M8's impeccable sound quality is established and proven in double-blind listening tests against the competition in Revel's world-class engineering facility. Before a Revel loudspeaker ever impresses a discriminating reviewer or thrills an audiophile, it has to satisfy the toughest audience of all – trained Revel listeners.

### REVEL CONCERTA M8

The M8 is a superb 2-way satellite surround or front-channel loudspeaker in the long-standing tradition of iconic Revel best-in-class sound reproduction. Featuring Micro Ceramic Composite (MCC) diaphragms, precision dividing networks, and sophisticated high-frequency waveguides, M8s are engineered to deliver movie and music sound of spectacular realism in any stereo or multichannel home theater system. Whether you enjoy immersing yourself in the majesty of a surround-sound movie soundtrack, or indulging in the magic of your favorite studio music or live performance, the M8 delivers. In addition, the speakers are magnetically shielded for safe placement near electronic devices.



# VIRTUALLY UNLIMITED CHANNEL CONFIGURATIONS AVAILABLE



#### M8 SP2 Package

A sleek 2-channel system for your home theater sound

- Two vertically-oriented M8 satellites
- Surface and wall-mounting hardware for superb flexibility with positioning options

#### M8 SP5 Package

A powerful 5-channel home theater surround system, including a center channel speaker to provide the heartbeat of your audio experience

- Four vertically-oriented M8 satellites
- One horizontally-oriented M8 center channel with table cradle and wall bracket for easy stationing
- Surface and wall-mounting hardware for superb flexibility with positioning options

Combine packages to create 7- and 9-channel systems and beyond, for legendary Revel home theater surround audio in nearly any size setting.

#### 3 Colors Available

The M8 SP5 and M8 SP2 are available in black, white and red automotive-grade high-gloss finishes, each with a color-matching cloth grille, for stylish and sophisticated appearance, and integration into a wide variety of decors.



#### **B8** Subwoofer

The Revel B8 powered subwoofer features an 8-inch down-firing cone transducer and built-in high-performance 200-watt amplifier for powerful, dynamic and accurate low-frequency performance that makes your audio entertainment come alive. Wireless audio signal transmission means you can place your subwoofer anywhere in your room without having to run a cable. The compact B8 is available in two high-gloss finishes, black and white, for easy integration into any home theater décor. Combine it with an M8 SP5 satellite package for a complete Revel surround system at unprecedented affordability.





# SPECIFICATIONS

REVEL M8 SATELLITE LOUDSPEAKERS	
Frequency Response (+/-3dB)	110Hz – 21kHz
Recommended Amplifier Power Range	10 – 125 Watts
Sensitivity (2.83V @ 1m)	88dB
Nominal Impedance	8 Ohms
Crossover Frequency	2.2kHz
Low-frequency Drivers	Dual 3" (76mm) woofers with MCC cones
Low-frequency Extension	-3dB @ 110Hz; -6dB @ 100Hz; -10dB @ 90Hz
High-frequency Driver	1" (25mm) tweeter with waveguide and MCC dome
External Dimensions (H x W x D)	11 5/8" x 4 1/4" x 4 1/2" (296mm x 107mm x 113mm)
Net Weight per Speaker	3.45 lbs (1.6kg)

REVEL B8 WIRELESS SUBWOOFER	
Low-frequency Transducer	8" (200mm) down-firing cone
Amplifier Power	200 Watts (continuous), 400 Watts (peak)
Frequency Response	45Hz – 200Hz
Controls	Volume, Phase, Base Boost
Connections	LFE (RCA-type); left and right line-level (RCA-type)
Enclosure Type	Sealed
External Trigger Input Voltage	3-30 Volts, AC or DC
Subwoofer Power Requirement	120V, 60Hz (USA), 220V – 240V, 50/60Hz (EU)
Subwoofer Power Consumption	< 0.5V
Subwoofer Dimensions (H $\times$ W $\times$ D)	13 29/32" x 10 1/2" x 10 1/2" (353mm x 267mm x 267mm)
Subwoofer Weight	19.8 lbs (9kg)
Transmitter Power Requirement	100 – 240V AC, 50/60Hz
Transmitter Power Consumption	< 0.5W
Transmitter Unit Dimensions (H $\times$ W $\times$ D)	1 3/8" x 5" x 3 1/2" (35mm x 127mm x 89mm)
Transmitter Unit Weight	0.26 lbs (117g)
Frequency Range	2403 – 2472MHz
Max Transmitting Power	10dBm



HARMAN International Industries, Incorporated 8500 Balboa Boulevard, Northridge, CA 91329 USA

© 2017 HARMAN International Industries, Incorporated. Revel and the Revel logo are trademarks of HARMAN International Industries, Incorporated registered in the United States and/or other countries. All rights reserved. Features, specifications and appearance are subject to change without notice.

