

The SunBrite logo is displayed in a white, serif font on a yellow rectangular background.A large SunBrite TV is mounted on a patio overlooking a lake. The screen shows a football game. The patio is furnished with outdoor seating and a fire pit, with warm lighting in the background.

Our Strongest and Brightest SunBrite TV Ever

SunBrite Pro 2 Series Full Sun 1080P 1500 NIT Outdoor TV

Made to be one of the brightest and most durable TVs on the market, the SunBrite Pro 2 provides the ultimate viewing experience in active and high-traffic areas. From its incredibly brilliant edge-to-edge display to its weatherproof frame, the Pro 2 gives you a sleek looking TV that can handle the harshest environments.



Super-Bright 1080p HD

With TruVisionPro anti-glare technology and 1500 NITS of 1080p HD clarity, you get a brilliant display on the brightest days. Indoor TVs only provide 100-300 NITS, which makes clear outdoor viewing impossible.

Built for Active Environments

With an impact-resistant display and EST technology to guard against isotropic blackout, the Pro 2 is perfect for active environments, including high-traffic bars and amusement parks, rambunctious poolside patios, and more.

Made for Permanent Outdoor Installation

Featuring a weatherproof aluminum frame that keeps the elements out, and a weatherproof media bay with an innovative cable entry system, the Pro 2 provides year-round entertaining that's independently certified for safe outdoor use.

VISIT US AT
www.sunbritetv.com

	SB-P2-32-1K-BL	SB-P2-43-1K-BL
Color	Black	Black
Backlight Compensation	1500 nits (cd/m2)	1500 nits (cd/m2)
Audio Output Connectors	Built-in 10W x 2 audio amplifier Optical Toslink Analog 1/8" headphone jack (Variable)	Built-in 10W x 2 audio amplifier Optical Toslink Analog 1/8" headphone jack (Variable)
VESA Mounting Pattern	100mm x 100mm, 200mm x 200mm	200mm x 200mm
Finish	Powder-coated Aluminum	Powder-coated Aluminum
Power Consumption	100-240 VAC, 50-60 Hz 2.0 A Max (127 Watts/1.1a@120v)	100-240 VAC, 50-60 Hz 2.0 A Max (127 Watts/1.1a@120v)
HDMI Connections	2x (HDMI 2.0, HDCP 2.2, HDMI 1.4 & HDCP 1.4a)	2x (HDMI 2.0, HDCP 2.2, HDMI 1.4 & HDCP 1.4a)
HDBaseT Connections	1 x (RJ45 - single Cat5e/Cat6 cable)	1 x (RJ45 - single Cat5e/Cat6 cable)
Video Inputs	1x RF Antenna/CATV (ATSC/QAM/NTSC) 1x YPbPr + L/R Audio 1x Composite + L/R Audio 1x 15-pin D-sub VGA + L/R Audio	1x RF Antenna/CATV (ATSC/QAM/NTSC) 1x YPbPr + L/R Audio 1x Composite + L/R Audio 1x 15-pin D-sub VGA + L/R Audio
Screen Resolution	1920 x 1080 1k (supports 4k downscaling)	1920 x 1080 1k (supports 4k downscaling)
Aspect Ratio	16:9	16:9
Screen Description	32-inch diagonal Color Active Matrix TFT LED LCD	43-inch diagonal Color Active Matrix TFT LED LCD
Contrast Ratio	3000:1	3000:1
Frame Rate	60 Hz	60 Hz
Panel Viewing Angle	178° x 178°	178° x 178°
Response Time	8 milliseconds	8 milliseconds
TV Formats	2160p*,1080p, 1080i, 720p, 720i, 480p, 480i *using hdmi only	2160p*,1080p, 1080i, 720p, 720i, 480p, 480i *using hdmi only
Control Set	RS232 Serial, Discrete IR Control, Concealed rear IR Window, IP Control, OvrC	RS232 Serial, Discrete IR Control, Concealed rear IR Window, IP Control, OvrC
Included Speaker	None, but compatible with all SunBrite Soundbars sold separately	None, but compatible with all SunBrite Soundbars sold separately
Operating Temperature	-24°-122°F	-24°-122°F
Non-Operating Temperature	-24°-140°F	-24°-140°F
Dimensions (W x H x D)	30.35" x 18.32" x 4.49"	39.62" x 23.45" x 4.57"
Weight	41 lb	69 lb