



XIO BLUETOOTH ENDPOINTS

PoE-powered, Dante-enabled endpoints with high performance audio quality for the connection of user supplied devices.

OVERVIEW

Symetrix xIO Bluetooth provides flexible wall mounted connectivity with best in class audio performance.

xIO Bluetooth provides simple convenient Bluetooth I/O and the xIO Bluetooth RCA-3.5 adds additional flexibility with stereo RCA and 3.5 analog I/O.

Both models have a clean, sleek design available in black or white and are compatible with standard Decora faceplates.

Full-featured Bluetooth 5.0 chipset provides extended range, stable connections, and premium audio quality.

Control is extremely flexible with Symetrix remotes and touchscreen panels, or user supplied devices.

Complete configuration and programming is fast and efficient from within the Symetrix Composer® Design, Configuration, and Control software application for integration with Symetrix IP DSPs.

KEY BENEFITS

Analog Inputs

The flexible stereo RCA and 3.5mm jacks provide unbalanced analog inputs with high quality gain control, flexible routing, and can be configured for full stereo operation or various mono sum combinations, offering convenient connection of user-supplied devices.

Bluetooth Functions

Features include media-only connectivity, phone bridge only connectivity, or both. PIN code Bluetooth security and selectable single or multiple memorized Bluetooth pairings meet a full spectrum of user requirements.

Device Integration

Designing, programming, and installing including Dante routing is easy with the Symetrix Composer software just like the rest of the system. This eliminates the use of another piece of software or the need to configure them using hardware.

Standard Fit

The convenient 1-gang and 2-gang standard US and EU wall box form factors available in black or white with Decora faceplates provide the right amount of I/O in the right locations to get the job done.

Flexible Control

All aspects of the two models of xIO Bluetooth are easily controlled from Symetrix wall remotes and touchscreens, as well as user supplied devices, all without any special training or instruction.

Easy Connectivity

With PoE integration, installation is simplified with only one cable needed for connection to a PoE enabled network switch.

PRIMARY CAPABILITIES

- Bluetooth 5.0
- 4 channels of Dante IO on RCA-3.5 model
- Selectable Bluetooth modes: Media only, Phone only, Both
- PIN code Bluetooth security
- Selectable single or multiple memorized Bluetooth pairings
- LED blackout mode
- Dante-enabled with sampling rates up to 48K
- PoE
- Programmable with Symetrix Composer software
- Decora-compatible faceplates that snap into place without visible screws
- Premium light and dark finishes
- Q-SYS compatible via Symetrix plug-in



xIO Bluetooth



xIO Bluetooth RCA-3.5



APPLICATIONS

- Venues
- Hospitality
- Business
- Education
- Government
- Worship

COMMON USE CASES

- Access audio sources from many locations around spaces with temporary connections.
- Enable DJ's to patch in mixers and speakers to augment sound reinforcement.
- Use media-only and phone bridge only connectivity to ignore one or the other connections.
- Route audio media output from personal devices into conference audio systems.
- Include microphones, external mixers, playback sources, and personal devices as input connections.
- Include computer audio interfaces for streaming or recording as outputs.
- Use laptops, media players, or smart phones to play back pre-recorded music, cues, or announcements.
- Supports recording and playback workflow interconnecting computers for storing and logging audio.
- Install at the front, back, or wings of spaces for complete user flexibility.



WHERE IMMERSIVE AV EXPERIENCES BEGIN

www.symetrix.co | +1.425.778.7728 | marketing@symetrix.co

© 2025 Symetrix, Inc. All rights reserved. All specifications are subject to change. MS-05B

