

D-Mic 70 SL

Directional Microphone, 70 cm



Description

The removable gooseneck microphone is equipped with a screw lock connector for easy connection to the different delegate and interpreter units.

Its unidirectional response results in optimal performance even in environments with a lot of ambient noise. The gooseneck design also allows for a large freedom of movement.

Another important advantage is the very low susceptibility to interference from mobile phones.

Finally, the D-MIC SL microphones deliver a rich, natural sound. It enables longer and more comfortable meetings where participants experience less strain produced by traditional artificial and mechanical microphone sounds. The light ring is dark (opaque) when the microphone is switched off, it lights up red when active, and green when in request.

The D-MICxxSL is available in a 30, 40, 50 and 70 cm version, as well as in a fully flexible 40 cm version. It is important to note that the D-MIC 70 SL must always be mounted vertically and cannot be used on angled delegate units.



To prevent any damage during transportation and storage, the microphones should always be handled in a horizontal position in their packaging.

Specifications

Mechanical

Material	Brass
Color	Matt black, RAL 9011
Size (mm)	705 (w) × 25 (h) × 25 (d)
Size packed (mm)	765 (w) × 50 (h) × 50 (d)
Weight	135
Weight packed	250
Diameter of the stem	Flexible part: 8 mm Rigid part: 6.3 mm

Electrical

Transducer principle	Back electret (condenser)
Operating principle	Pressure gradient
Polar pattern	Unidirectional, cardioid
Nominal conditions	Bias resistor = 1k2 Vdd = 3.3 V DC 1 Pa = 94 dB SPL
Max SPL @ 1 kHz	110 dB SPL (1% THD+N)
Signal to noise ratio	> 67 dB(A)
Free field sensitivity	(-40.5±2) dBV @ 1Pa, 1KHz
Power supply	3.3 V DC, 0.5 mA
Consumption	0.5 mA (without LED ring) Max 25 mA (with LED ring)
Connection	Screw lock

Certification

Region	Certification
Europe	CE

