

CRST-1

2X18AWG shielded + 2X22AWG unshielded



Construction:

2X22AWG shielded + 2X18AWG unshielded

	2X22AWG shielded:	2X18AWG unshielded
Cond. Material:	Oxygen Free Copper Wire	
AWG:	22 (7*0.25mm)	18 (16*0.25mm)
Insulation Diameter:	2.0mm +/- 0.2mm	1.95mm +/- 0.2mm
Insulation thickness:	0.60 +/- 0.15mm	0.35 +/- 0.10mm
Insulation color	White / Blue	Red / Black
Al-foil shielding	Y	N
Drain wire:	24AWG (7*0.20TC)	N
Impedance	100 +/- 15 Ohms	/
Capacity	11 +/- 2 Pf/feet	/
Ripcord:	Nylon (150D)	
Overall jacket:	PVC	
Diameter:	5.9 +/- 0.4mm	
Thickness:	0.60 +/- 0.2mm	
Color:	Pantone 326 C (w/ yellow stripe).	

Mechanical characteristics:

Min. Bending Radius: 20 X ϕ
 Operation Temperature (degree): 75

Cable marking:

Binary™ by SnapAV, CRST1, E325177 (UL) C(UL) CMG/CM FT-4, 2x22AWG SHIELDED + 2x18AWG UNSHIELDED, DDMMYY, xxxFT (INCREASE & DECREASE)